



Flexi AC 1000

1700kg rated capacity

Create up to 30% more warehouse capacity

Flexi AC 1000 works in just 1642mm (EURO) or 1762 (ISO) aisles to BITA GN9 (FEM) standards. Handles Euro Alliance pallets in 2m aisle to DNN 15185 standard.

Lift heights to 8.5 metres

Designed to bring Flexi articulated space saving and handling efficiency to users of all popular pallet types.

Stacking performance

Unique 1000mm wide chassis and "Artic" 220° over rotate feature allow block stacking of pallets and drive in rack operation.


Triplex or duplex mast

Lift mast options include triplex full free lift or duplex limited free lift, to suit most warehouse locations.

 **AC 1000 / 1100**



COMPACT FRONT AXLE AC POWER



Latest AC drive technology for fast acceleration and safe controlled braking. Integrated fault finding and monitoring. Easy turning in very narrow aisles.

FORWARD FACING SEAT



High quality adjustable full suspension seat with operators lumbar support.

EASY BATTERY CHANGE



Low rear lift off or roll off for fast changeovers. Good access for battery topping. No motors or components underneath.

'HIVIS' OVERHEAD GUARD



The unique 'Hi Vis' twin post safety guard combines maximum visibility and overhead protection for the operator.

AC 1000 STANDARD FEATURES

- 220° Articulation
- 'True Radius' safe turning
- Ultra narrow chassis
- CCTV / LCD system option

STEEL PLATE REAR COVER



Detailed steel plate rear panel protects traction battery. Narrow 1000mm wide rear chassis allows block stacking and drive in rack operation. Handles Euro alliance pallets in 2 metre aisle to DIN I51.

TOUGH SUPER-ELASTIC TYRES



Flexi AC 1000 super-elastic front drive wheels provide excellent grip and traction in all conditions when fully loaded. Resistant to damage and premature failure.

TILTING "CLEAR VISION" MAST



Flexi's famous "clear vision" triplex mast design, heavy duty German cold rolled 'I-beam' sections format. Integrated heavy duty side shift fork carriage is standard.

PARCEL BAY



Conveniently located behind the operator and suitable for carrying a roll of plastic film or any other material that needs to be close to hand.



FLEXI NARROW AISLE

